

MIRROR

SERVICE DATA

Outer mirror switch assembly	Resistance: L position 4 - 8: Below 1 Ω at switch position UP 6 - 7: Below 1 Ω at switch position UP 4 - 7: Below 1 Ω at switch position DOWN 6 - 8: Below 1 Ω at switch position DOWN 5 - 8: Below 1 Ω at switch position LEFT 6 - 7: Below 1 Ω at switch position LEFT 5 - 7: Below 1 Ω at switch position RIGHT 6 - 8: Below 1 Ω at switch position RIGHT Resistance: R position 3 - 8: Below 1 Ω at switch position UP 6 - 7: Below 1 Ω at switch position UP 3 - 7: Below 1 Ω at switch position DOWN 6 - 8: Below 1 Ω at switch position DOWN 2 - 8: Below 1 Ω at switch position LEFT 6 - 7: Below 1 Ω at switch position LEFT 2 - 7: Below 1 Ω at switch position RIGHT 6 - 8: Below 1 Ω at switch position RIGHT
------------------------------	--

SS

TORQUE SPECIFICATIONS

Part Tightened	N*m	kgf*cm	ft.*lbf
Outer rear view mirror assembly x Front door panel sub-assembly	8.0	80	71 in.*lbf
Negative battery terminal x Battery	3.9	40	35 in.*lbf